

OPTIMAL® Rotating brushes for excavator

Optimal® rotating brushes for excavators are designed to be efficient and easy to maintain. Two hydraulic engines guarantee that the sweeper rollers rotate evenly, even in situations where the brush is pressed exceptionally hard against the ground.

The standard equipment includes mudguard and support legs to facilitate in storage.



Technical specifications

| Model | PH 100 | PH 150 | PH 180 | PH 220 | PH 270 |
|-----------------------------------|-------------|-------------|-------------|-------------|-------------|
| Operating width (A) | 100 cm | 150 cm | 180 cm | 220 cm | 270 cm |
| Width (B) | 135 cm | 185 cm | 215 cm | 255 cm | 305 cm |
| Height (D) | 120 cm | 120 cm | 120 cm | 120 cm | 120 cm |
| Diameter (E) | 90 cm | 90 cm | 90 cm | 90 cm | 90 cm |
| Recommended oil flow | 55 l/min | 55 l/min | 55 l/min | 55 l/min | 70 l/min |
| Oil pressure (min-max) | 160-230 bar | 160-230 bar | 160-230 bar | 160-230 bar | 160-230 bar |
| Weight (without connecting frame) | 190 kg | 235 kg | 260 kg | 290 kg | 330 kg |

Standard equipment

Mudguard
Support legs (2)

Options

| |
|--|
| Connecting frames: |
| - S40 |
| - S45 |
| - S50 |
| - S60 |
| - NTP10 |
| Hydraulic flow limiter (required for flow over 80 l/min) |

